



ELECTROGUARD

ANTI STATIC PAINT

ELECTROGUARD A40® - TECHNICAL DATA **Water-Based Acrylic Static Dissipative Coating**

A Single Pack Acrylic paint designed for application in static sensitive areas. This material is water based with low odour and can be safely applied by maintenance personnel without specialist knowledge of flooring systems.

Two coats are recommended for best results and should be applied over a sound, sealed surface, free from dirt, oil or any loose particles. To comply with the electrical specification it is strongly recommended that A40 is not applied directly over bare concrete. Where this occurs a Water Based Primer should be first applied.

Physical Properties:

Typical Thickness:	40 microns per coat
Drying @ 20C:	We recommend 2 thin coats, do not over apply thickness Touch Dry 2 Hrs Re-Coat at 8 Hrs Full Cure 3 Days
Pot Life:	12 months
VOC Content:	60.5g / litre
Coverage:	10m ² /Litre per coat (we recommend 2 coats)
Mix Ratio:	Ready Mixed
Thinner:	We do NOT recommend thinning this paint
Colour:	Signal Grey (RAL 7004) - Other colours are available
Pack Size:	5 litres
Transportation:	No Hazard issues

Limitations:

Do not apply if Temperature is below 10C. Moisture content of concrete surfaces should be less than 15%. Curing times are dependent on temperature, humidity and ventilation.

Electrical Properties:

Surface Resistance:	10(5)-10(8) Ohms/Square
Resistance to Ground:	10(5)-10(8) Ohms Conforms to IEC 61340-5-1/2
Charge Decay:	Conforms to MILB81705C

www.electroguardpaint.com